

HUELSTA.COM



FENA LIVING

Contents

oontonto	Page
Range introduction, lists of versions, important notes	2-3
Special combinations	4
Suggested combinations	6-9
3 Raster lowboards	10-11
3 and 4 Raster TV centre, (wall) extendable lowboards for TV centre	12-13
Media accessories for lowboards, flat screen supports	14-15
4 Raster sideboards	16-17
8 Raster highboard, 12 Raster cabinet	18
Wall units	19
Wall shelves, LED lamps for wall shelves	20
Accessories for drawers, fitted shelves	20-21
Lamps, radio remote control	22
Dining, coffee tables	23
General information:	
Switch options for lamps	24-25
Cable apertures	26
Special-sized products, special articles	27
Important notes: quality of walls / assembly instruction	28

A perfect fusion of originality and modernity.

Perfect balance provided by striking contrasts – how does that work? Easily. By mixing apparent contrasts. FENA proves that very different and very original materials can be perfectly combined in a balanced design. Accents in concrete grey, bronze and natural planked oak team up with elegant matt lacquer to create a monolithic architecture that is both archaic and futuristic. Horizontal lines offer tranquillity, the square provides a balancing counterweight.

Using impressively pure materials and featuring clean and simple lines, FENA offers an utterly stylish fusion of apparent contrasts. Functional units add striking highlights to the living room.

A stunning mix of lacquer, wood, concrete and bronze:

Accents in concrete grey and bronze as well as rustic planked oak team up with elegant matt lacquer in a balanced furniture architecture – original yet futuristic.

A balanced design:

An emphasis on horizontal lines within a regular geometry ensures a laid-back look - continuous veneer pattern in the fronts.

Distinctive media talent:

TV centre in concrete grey and bronze as a visual contrast and appropriately sized lowboards for a perfect integration of large flat screens and standard integrated cable apertures.

Lists of versions

Model no.	Carcase and front	Price group	Model no.	Accent
648 663 695	Pure white lacquer Silk grey lacquer Planked oak	I I II	656 672	Concrete grey Bronze
Note: Inner carcase and interior fittings always in pure white lacquer.				rey and bronze accent versions are only available for chosen compo- re specially marked.

Changing versions:

With FENA units it is also possible to order the cover shelf and the rear wall of the 12 Raster cabinet in a different version (without surcharge). Please state clearly in the order.

Versions of handles and metal substructures

Handle versions

Handles optionally in high-gloss chrome or antique silver

Metal substructure versions

Metal substructures optionally in high-gloss chrome, antique silver or bronze

Please state all the required versions clearly in the order!

Range introduction

Important notes

Changing versions: With FENA units it is also possible to order the cover shelf in a different version (without surcharge). Please state clearly in the order.

Accent:

The concrete grey and bronze accents are only available for chosen components. These are specially marked

Handle versions:

Handles optionally in high-gloss chrome or antique silver. Please state the required version clearly in the order!

Metal substructure versions:

Metal substructures optionally in high-gloss chrome, antique silver or bronze. Please state the required version clearly in the order!

Glass versions:

Glass doors and door panels of bronzed glass and glass shelves behind their fronts of satinised glass

Standard interior fittings:

1 fitted shelf is fitted behind 3-4 Raster high doors.

Drawer frames in grev

Wall units: Wall units always incl. wall bracket

Combinations of floor and wall units:

If floor and wall units are combined within an arrangement, there must not be any skirting boards in the room near the floor units, otherwise they must be removed.

Max. load:

Max. load of wooden and glass shelves (up to 70.4 cm width) as well as drawers: 25 kg Max. load of wooden and glass shelves (between 70.4 and 105.6 cm width): 15 kg; from 105.6 cm width: 10 kg Max. load of cover shelves: 35 kg per metre length for floor units. Please also note any maximum loads which may be stated in the type list for the individual units!

hülsta-SoftFlow:

Drawers on hidden roller bearings with automatic cushioned closing device, fully pull-out.

Labelling in type list drawings / assembly notes for wall units

Labelling in type list drawings / assembly notes for wall units The majority of units have two wall mounting points (= number of base plates), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= base plates) is required, this is marked in the drawings in the type list with numbers in black boxes. Please be sure to note here the information and notes in the "Wall composition" chapter!

Notes on delivery

Notes on delivery:

3

4

The majority of the units are delivered standard as fully connected units (glued) so that the carcase cannot be disassembled. There are however some exceptions to this rule:

Some carcases are delivered as complete units but can be **disassembled into** individual sections in the final customer's home. These types are marked with 1 a 1 in the type list.

Some carcases are delivered in individual sections because of their size. 2 These types are marked with a 2 in the type list.

The fronts with the number 2 are delivered separately and can therefore always be (dis-) assembled


Wall fitting

Important notes: Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units. That is why wall mounting should only be carried out by properly trained and qualified fitters. hülsta supplies materials for mounting units on walls for nearly all the units and which should be used for safety and for constructional reasons. The assembly materials supplied by hülsta (plugs, screws) are only suitable for fitting components on to concrete in firmness class C12/15. For other materials (please see separate materials table in the wall composition chapter) we provide you with an assembly mortar set as an extra order. Please note that this assembly mortar set is also only suitable for the materials listed in the materials table. If walls are made up of other materials (e.g. plastered or lighter wall materials), one should use another method of mounting better suited to the load on site. Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. For the reasons stated above it is absolutely essential to enquire about the composition of any walls before signing any contracts.

Information on the sketches

Order of markings


The markings for the fronts go from left to right and/or from top to bottom.



Special combinations

4

Please state the required handle version clearly in the order!




Wohnen: Fena






E 9.2021

Please state the required handle version clearly in the order!




Wohnen: Fena

E 9, 2021




Please state the required handle version clearly in the order!



E 9.2021

8





E 9.2021

3 Raster lowboards



Cover shelf of lowboards optionally available in **concrete grey** and **bronze** versions (without surcharge). Please state clearly in the order!





E 9,2021

TV planning units



Carcase of 3 and 4 Raster TV centre optionally available in **concrete grey** and **bronze** versions (without surcharge). Please state clearly in the order!

3 Raster TV centre for extendable lowboards

3 Raster TV centre for extendable lowboards 54.2 cm high (56.0 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep			3 Raster TV centre for	r extendable lowboards	
incl. cable aperture K8 in cover shelf and K20 in the carcase sides. Further cable apertures K20 are possible.					
The 3 Raster TV centre must be fitted between extendable lowboards (see below).			Compart rear wall	ment with niche for connections	
L/R = Door hinge left/right					
				m wide door	
			040	111 L	
	Price gr. I			- -	
Extendable low	narde	s for 3 Raster TV		Cover shelf of lowboards optionally avai versions (without surcharge). Plea	lable in concrete grey and bronze ase state clearly in the order!
Extendable lowboards for 3 Raster TV centre 54.2 cm high (56.0 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep					
incl. cable aperture K20 on the side which is fitted to the TV centre. Further cable apertures K20 are possible. Handles:		73.3 cr	L n wide	73.3 C	L m wide
See here the information on page ${f 3}$		2 da	Dors	2 drawers	1 flap; 1 drawer
TV centre and extendable lowboards must be ordered in combination.					
L/R = Extendable on the left/ right side of the TV centre	Ext. left Ext. right Price gr.	3703 3703		37011 L 37012 R	37081 L 37082 R
	1	-		-	-
					2
		143.7 c	m wide 1 flap; 1 drawer	214.1 c 2 doors; 2 drawers	m wide 2 doors; 1 flap (top), 1 drawer
			, nap, i ditavoi	2 00013, 2 010W013	2 00013, 1 hap (00µ), 1 01aWel
	Ext. left Ext. right Price gr.	314011 L 314012 R -	314081 L 314082 R -	321031 L 321032 R -	321081 L 321082 R -

TV planning units

Notes on delivery:1Please see here the information on range introduction2 pages.

Assembly notes for wall units: Please be sure to note here the information and notes in the "Wall composition" chapter! 5

FENA

4 Raster TV centre for extendable wall lowboards

		CALCHUADIC Wall	1044504145			
4 Raster TV centre for extendable wall lowboards TV centre 67.0 cm high (68.8 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep Storage shelves 55.7 cm wide, 35.0 cm deep; max. load 5 kg; height between storage shelf and wall extendable lowboard: 10.6 cm incl. cable aperture K8 in cover shelf and K20 in the carcase sides. Further cable apertures K20 are possible. The 4 Raster TV centre must be	4 Raster TV centre for extendable wall lowboards					
fitted between wall extendable lowboards (see below).						
L/R = Door hinge left/right			TV centre 35.2 cm wide: total wi	dth incl. storage shelves: 146.6 cm		
				door	·	
			340)21 L		
	Price gr. I			222 R - -		
Extendable wall lowboards for 4 Raster TV Cover shelf of lowboards optionally available in concrete grey and bro						
centre			ACCENT	versions (without surcharge). Ple	ase state clearly in the order!	
Extendable wall lowboards for 4 Raster TV centre 36.6 cm high 45.0 cm deep incl. cable aperture K20 on the side which is fitted to the TV centre. Further cable apertures		55.7 cr	L n wide	73.3 c	L m wide	
K20 are possible.		1 drawer	1 flap	1 drawer	1 flap	
Handles: See here the information on page 3	Ext. left Ext. right	25011 L	25081 L	27011 L	27081 L 27082 B	
TV centre and extendable wall lowboards must be ordered in combination.	Price gr.	25012 R - -	25082 R - -	27012 R - -		
L/R = Extendable on the left/ right side of the TV centre Max. load: 55.7 cm width: 7.5 kg 73.3 cm width: 10.0 kg 143.7 cm width: 20.0 kg 196.5 cm width: 27.5 kg		ی ا 143.7 c	3 L m wide	196.5 0	2 5 L cm wide	
		1 drawer	1 flap	2 drawers	1 flap; 1 drawer	
	Ext. left Ext. right Price gr.	214011 L 214012 R -	214081 L 214082 R -	219011 L 219012 R -	219081 L 219082 R -	
	II	-	-	-	-	

Lamps for extendable wall lowboards for 4 Raster TV centre

LED light strip	2.2 W		4.1 W	9.3 W	11.5 W
flush mounted			Des Same		
This luminaire contains built-in LED lamps of the energy classes A++ to A. The lamps cannot be changed in		T	715-715	711-711-711	THE AND
the luminaire. 12 V		for 55.7 cm width	for 73.3 cm width	for 143.7 cm width	for 196.5 cm width
		522	702	1402	1902
		-	-	-	-
Wohnen: Fena E 9. 2021			·	•	

IR repeater set

IR repeater set

Infrared signal transmission set for operating media units behind wooden/lacquered fronts. You can operate all the units in one compartment with one set. The following applies:
One set must be used in each compartment. 2 transmitters can also be installed in large compartments in order to increase performance. In this case only one additional transmitter needs to be ordered.
The transmitter must be placed in the direct vicinity of the receiver eye.

- Transmittable IR frequency band 20 60 kHz
- Up to 3 transmitters can be combined with one receiver.

It is possible to use 3 transmitters via 1 receiver including Master box. This enables simultaneous operation of 3 different furniture compartments or in critical situations it allows fitting out one furniture compartment with several transmitters in order to increase the performance in this compartment or to operate 2 end units placed next to one another.

The IR repeater set consists of:

- 1 receiver eye (Ø 3.0 cm) incl. standing bracket
- 1 electrical transmitter
- 1 plug EVG 12 V
- Cable clips

Please note the details stated in the operating instructions!

IR repeater set 1 receiver eye and 1 transmitter incl. standing bracket 2001 -Extra transmitter

2003

Cable apertures / subwoofer base cut-out section

	Cable aperture K1 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear of the top shelf. The position is in the centre of the compartment, distance from centre of aperture to rear edge of unit: 10.0 cm.	K1
° -	Cable aperture K2 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the rear wall of the lowboard. Positioned in centre of compartment.	K2
	Cable aperture K7 silver-coloured; 7.0 x 12.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The position is in the centre of the compartment, flush with the rear edge of the unit.	K7
	Cable aperture K8 silver-coloured; 12.8 x 3.2 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear rim of the top shelf. Positioned in centre of compartment.	K8 -
	Cable aperture K9 13.0 x 1.6 cm It is possible to fit a cable aperture in a fitted shelf. The cable aperture can be made at the rear rim of the fitted shelf. Positioned in centre of compartment.	K9 -
	Cable aperture K20 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the partitions of the lowboard.	K20
	Subwoofer base cut-out section Base cut-out section 12 x 23.2 cm The sounds from the subwoofer pass out through the base cut-out section in the lowboard without hindrance. The exact position in the carcase is predetermined ex-works and cannot be altered.	14 -


Flat screen supports


Flat screen support WTL6 The flat screen support can be adjusted 3-dimensionally. It is suitable for flat screens with a screen diagonal of 102- 216 cm (40°-85°); max. load: 45 kg. Suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 200 x 200 mm max.: 600 x 400 mm	Flat screen support THIN 545, ideally adaptable The flat screen support can be adjusted 3-dimensionally. It is suitable for flat screens with a screen diagonal of 81- 140 cm (32"-55") and a maximum depth of 4.5 cm; max. load: 25 kg. Go to www.vogels.com to check if your flat screen can be fitted on this flat screen support. Enter the name THIN 545. After a few steps you can see if your flat screen TV is compatible with the flat screen support. Not suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 100 x 100 mm max:: 600 x 400 mm	Flat screen support THIN 515 The flat screen support can be angled up to a max. 15°. It is suitable for flat screens with a screen diagonal of 102- 165 cm (40°-65°) and a maximum depth of 5.0 cm; max. load: 25 kg. Go to www.vogels.com to check if your flat screen can be fitted on this flat screen support. Enter the name THIN 515. After a few steps you can see if your flat screen TV is compatible with the flat screen support. Not suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 100 x 100 mm max.: 600 x 400 mm
for fitting anywhere on walls	for fitting anywhere on walls	for fitting anywhere on walls
9704 -	9304 -	9504 -

4 Raster sideboards



Cover shelf of sideboards optionally available in **concrete grey** and **bronze** versions (without surcharge). Please state clearly in the order!







E 9,2021

17

8 Raster highboard






Wall shelves

Wall shelves 2.9 cm thick 23.4 cm deep for fitting anywhere on walls					
Integrated LED spotlamps (see page 22) and LED lamps (see below) are possible from 70.4 cm width.					
		52.8 cm wide	70.4 cm wide	105.6 cm wide	140.8 cm wide
		5224	7024	1024	1424
	Price gr. I	-			

LED lamps for wall shelves




Accessories for drawers

	for 35 cm front width	for 52 cm front width	for 70 cn widt		for 105 cm front width	for 1/2 drawer, 140 cm wide
Tableau lined with grey fabric	8624	8625	862	6	8627	8626
Cutlery box of metal, lined with grey fabric inside; incl. compart- ments		7.6 cm wide 855			35.2 cm wide 856	
Cutlery holder lined with grey fabric, for fitting in drawers Set 1: for 60 pieces of cutlery Set 2: for 17 serving utensils	Set 1: for standard (- cutlery like spoons, fork etc.	s, knives,	Set 2: for	- r sauce ladles, cake for	ks, cake servers, etc.
		116 -			117	

Fitted shelves

FENA



Lamps

This luminaire contains built-in LED lamps of the energy classes A++ to A. The lamps cannot be changed in the luminaire. 12 V			emote control is possible for operation (against a surcharge).		
N //			for 35 cm front width	for 52 cm front width	
behind wooden shelves	LED light panel 1.9 cm thick, 3.0 cm deep; for fitting in units		2.4 W	3.5 W	
under glass shelves			363	523	
			2.4 W	3.5 W	
A A A A A A A A A A A A A A A A A A A	LED glass rim lamp 1.0 cm thick, 1.1 cm deep; LED light strip in aluminium profile, for fitting behind fitt	ed glass shelves			
			364	524 -	
			2.9	W	
	Integrated LED spotlamp				
9	Ø 7.1 cm		7941		

Radio remote control with change of colour temperature

The lamps are normally operated by an external foot switch. The colour temperature of the LED lamps is cold white if a foot switch is used. A 4-channel radio remote control is also available as an alternative, which is charged extra. Several lamps can be operated with each of the 4 channels. All 4 channels can be dimmed separately at the push of a button. The colour temperature of all 4 channels can be set to any level from cold white (approx. 6500 kelvin = the basic setting of the LED lamps) to warm white (approx. 2700 kelvin). If warm white is required, a radio remote control must be ordered. It is also possible to switch all channels on and off simultaneously with the "all on" or "all off" buttons. The radio remote control consists of one transmitter and one receiver. If several receivers are required because of the arrangement of the units, these and the corresponding cables are provided ex-works (no surcharge). The foot switch is omitted when the radio remote control is used.



2119

DINING Dining tables and chairs

DINING

hülsta offers a room concept to meet all requirements in comfort, beauty of form and attractiveness with a comprehensive collection of dining room tables and chairs.

The **dining tables** in a wide variety of sizes (with and without pullout function) in all wood surface versions and in contemporary designs, as well as the **dining chairs** that can be combined individually using different armrests, comfort features, high-grade cover fabrics (leather, textiles) and metal surfaces can all be found in the **"DINING**" type list.

Coffee tables CT 180

Coffee tables CT 180

The **CT 180** coffee table in sizes of 111×47.6 cm and 111×111 cm provides one or two drawers which are opened in opposite directions.

You will find the CT 180 coffee table as well as other coffee tables in the "Coffee tables" type list.

Coffee tables

Coffee tables

hülsta offers a comprehensive **collection of coffee tables**, which not only match the hülsta furniture ranges perfectly but can also be combined with other products that are available on the market. You will find these coffee tables in a number of designs, sizes and versions in the **"Coffee tables"** type list.







Radio remote control with change of colour temperature

The lamps are normally operated by an external foot switch. The colour temperature of the LE also available as an alternative, which is charged extra. Several lamps can be operated with e button. The colour temperature of all 4 channels can be set to any level from cold white (appr kelvin). If warm white is required, a radio remote control must be ordered. It is also possible to The radio remote control consists of one transmitter and one receiver. If several receivers are cables are provided ex-works (no surcharge). The foot switch is omitted when the radio remote	each of the 4 channels. All 4 channels can be dimmed separately at the push of a ox. 6500 kelvin = the basic setting of the LED lamps) to warm white (approx. 2700 o switch all channels on and off simultaneously with the "all on" or "all off" buttons. required because of the arrangement of the units, these and the corresponding
 The following points must be noted with the radio remote control: The receiver must be positioned behind a rear wall or under plinth shelves (at least 20 mm s The total wattage power of all lamps included per receiver must not exceed 30 W. 4 channels = 4 light groups 1 light group = x lights All lamps within a light group can be dimmed to the same brightness. The change of the colour temperature takes place for all lamps in all light groups. The radio remote control is not suitable for equipment operating on 110 V. 	space required under plinth shelves).
4-channel radio remote control with change of co	lor temperature
Light colour warmer Light colour colder Channel 1 to 4 (with dimmer function)	4-channel radio remote control with change of color temperature
All on	Type 2119 -

Examples of use (schematic diagrams)

Example 1

Lights inside a unit


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamp in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps in the open compartment

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlamp in the right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Example 2

Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamp and the LED light panels in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps and the LED light panels in the centre cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlamp and the LED light panels in the right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Example 3

Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamps in the left, centre and right cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the top LED light panels in the left, centre and right cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the bottom LED light panels in the left, centre and right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Cable apertures

It is possible to provide the cover shelves, side sections, shelves, etc, in units from nearly all the hülsta living room ranges with cable apertures so it is easier to feed cables of electronic equipment through these units. There are four different types of cable apertures to choose from, as listed here. Please be sure to follow the important notes. Cable aperture K1 Cable aperture K2 Cable aperture K3 Cable aperture K20 Cable aperture for 80 mm hole, silver colour Cable aperture for 60 mm hole, silver colour Cable aperture for 80 mm hole, silver colour Cable aperture for 80 mm hole, silver colour particularly suitable for rear walls and side particularly suitable for shelves and conparticularly suitable for side-panels and Standard cable aperture: particularly suitable for cover shelves, side sections and sections structional shelves (suitable to an extent for centre partitions shelves scart cables) Sizes: Sizes: Assembly height: 8 mm Sizes: Assembly height: 2x 8 mm Sizes: Assembly height: 21 mm Assembly height: 21 mm Outside diameter: 92 mm Outside diameter: 92 mm Inside diameter: 74 mm Outside diameter: 72 mm Inside diameter: 74 mm Outside diameter: 92 mm Inside diameter: 74 mm Diameter of hole: 80 mm Inside diameter: 54 mm Diameter of hole: 80 mm Diameter of hole: 80 mm Diameter of hole: 60 mm **K1** K2 **K**3 K20


IMPORTANT NOTES Please be sure to note!

Please be sure to state the **exact position** of the cable aperture in your order (always measure distances from the centre of the cable aperture). For **wall units** the cable aperture is only possible in the bottom position (due to the suspension brackets). With **cover shelves**, the position of the cable aperture is determined in the factory, in accordance with factors specific to the given range. The same applies to technical exceptions because of custom-based planning. The K 20 is positioned in the centre (depthwise) in the **side-panel**. Please state the exact height (centre of hole of cable aperture from bottom rim of side-panel). Subject to technical progress.

The **minimum distance** for the cable aperture (measured from the inside): 100 mm from the side and 70 mm from the rear (for horizontal surfaces) or 100 mm from the side and 70 mm from the base (for vertical surfaces). Please state if the aperture is to be fitted at the left, at the right or in the centre. **Standard position**: If no details of the exact position of the cable aperture are given in your order, the cable aperture is always fitted at the bottom centre or at the rear centre of the relevant surface,

Standard position: If no details of the exact position of the cable aperture are given in your order, the cable aperture is always fitted at the bottom centre or at the rear centre of the relevant surface, whereby the distances stated above still apply.

Caution! Please note that the cable aperture can not be fitted where there is an integrated or front spotlamp, centre partitions or a split rear wall. Please be sure to observe the following explanatory diagrams!



FENA

Special-sized products are possible on request. Please get in touch with your customer advisor.

Special articles

Cover panels for side and top panelling of fitted wardrobes (support con-struction and fitting materials must be acquired on site).

Basic price per order + price per m ² lacquer or veneer Veneer match with fronts can not be guaranteed.	9901 990	-
--	-------------	---

Individual special-sized products

If the special-sized product that you require is so unusual that it cannot be illustrated with the many special sized products that we already provide and charge for, then we will quote you the price using a 33 unit type factor. In your order please state for us the relevant enquiry number and the 33 unit type factor stated.

33

Special colours; Note on "Blue Angel" / Emissions label of DGM

Special colours

All the hülsta lacquer colours are possible for nearly all the hülsta ranges. Availability and prices on request.

Note on "Blue Angel" (RAL-UZ 38) and Emissions label of DGM (Class A)

It is possible that the requirements of the "Blue Angel" and the DGM Emissions Label cannot be met by some of the lacquer colours in price groups III and IV (see here the different lacquer versions in the NEO range), depending on the colour mix (surface ratio of these colours in the corresponding order). However, the legal requirements are definitely met in all cases!

Important notes

Wall composition / assembly instruction

Important notes:

The composition of walls must be ascertained before concluding a contract and be checked by a qualified fitter before assembly takes place.


Assembly may only be carried out by a qualified fitter under careful observation of the assembly instructions.

The plastic Rawl plugs supplied by hülsta as a standard set are only suitable for concrete \geq C12/15, if the wall composition and compression strength corresponds to the table below. Under no circumstances must a unit be assembled on light masonry.

Furthermore, we provide a mounting set with assembly mortar for the types of walls listed below (see assembly mortar set below). Again, assembly must be carried out by a qualified fitter under careful observation of the wall composition and assembly instruction. The compression strength levels stated below must be met under all circumstances.

Materials table

with a description of which sets are to be used with the following types of walls:



A different and more suitable type of mounting must be chosen by a qualified fitter in all other cases. hülsta cannot accept any responsibility for the choice of any other types of mounting! Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units.

Mounting sets

Labelling in type list drawings / assembly notes for wall units

The majority of units have two wall mounting points (= number of support boards), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= support boards) is required, this is marked in the drawings in the type list with numbers in black boxes. Every support board requires four mounting screws.

3 = 3 support boards

4 = 4 support boards, etc.

One assembly mortar set is sufficient for up to a maximum of 3 support boards or 4 wall side-panels.

Important note: Depending on the composition of the wall (see wall types illustrated above), assembly must be carried out using the special assembly mortar set and a standard trade mastic tool which are the basic essentials for safe and clean workmanship.

Standard set

The standard set consists of 4 plastic Rawl plugs and 4 mounting screws and is sufficient for 1 support board. The standard sets are included in the packet of fittings to match the number of support boards.

Assembly mortar set for up to a maximum of 3 support boards consisting of:

9x injection retaining sleeve 9x screw-in sleeve 1x injection cartridge 2x static mixer 1x assembly instructions

Please use the mounting screws from the standard set (supplied free of charge).

- Example of order:
- Add up number of support boards for all existing unit types
- Divide the sum by "3"
- Round up the result to a full number
- = Number of assembly mortar sets required

M2

Your Hotline to hülsta

Do you have any questions or require any alterations to your order confirmation? Do you have any questions on our products or your current order? Do you have any complaints about supplied goods or required replacement parts? Contact Telephone: +49 (0) 2563 / 86-1627 • email: orders@huelsta.com

Do you have any questions, suggestions or wishes for the **hülsta product seminars**? Contact Telephone: +49 (0) 2563 / 86-1493 • email: seminare@huelsta.com

hülsta Planning Service

Your furn plan planning is so complex that you need our support? We have created the hülsta Planning Service for this kind of situation. hülsta employees will check your planning as quickly as possible. The customer gets a planning that will inspire him!

hülsta Planning Service

Tel.: +49 (0) 2563 / 86-1060 Fax: +49 (0) 2563 / 86-1000 Mail: Planungsservice-Handel@huelsta.com Mondays to fridays from 9.00 a.m. until 5.00 p.m.

Special wishes? Come to us!

Maximum individuality! – Maximal flexibility! – hülsta makes most of your special wishes possible. And if you do have a wish which is not quite so easy to implement, just give us a call or send us a mail or a fax. We have our own hülsta "Special Wishes Team" who are there to help you realise just these customer requests. These colleagues are professionals when it comes to special products. They plan and calculate the products possible for you and even develop an alternative suggestion if the idea should turn out to be technically impossible.

Here is an overview of the hülsta range of special wishes:

- A lot of special products can be ordered simply via the type list
- Special-sized products are planned simply and professionally
- Competent colleagues advise you by phone, by fax and by mail
- You will be sent alternative suggestions if the idea is technically impossible
- Many special-sized products are available without a surcharge
- · Specially qualified carpenters and technicians implement your plans perfectly

hülsta Special Wishes Team Tel.: +49 (0) 2563 / 86-1060

Fax: +49 (0) 2563 / 86-1000 Mail: Sonderwunsch@huelsta.com

We are open Saturdays for you, too!

Our Saturday hotline is available from 10.00 a.m. until 5.00 p.m.

Telephone: +49 (0) 2563 / 86-1800

The hülsta Sales Department is available mondays to fridays from 9.00 a.m. until 5.00 p.m.

hülsta FENA Wohnen

Stand: E 9. 2021

Design and concept legally protected, subject to error and alterations to construction, colour and materials by way of technological progress.

> hülsta-werke · Karl-Hüls-Straße 1 · D-48703 Stadtlohn Tel. +49 (0) 2563 / 86-0 · Fax +49 (0) 2563 / 86-1000 www.huelsta.com

