

PERSIS

LIVING





PERSIS

As a solid wood range, **PERSIS** combines finesse and grandeur with elegance and raw natural beauty. Strong solid wood perfectly encompasses opaque glass elements that give the appearance of shimmering wood. This extravagant effect is achieved using a world innovation in furniture design: a velvety soft relief in the glass fronts, coloured from the rear, which adds a sensational impact to the living room. In two colour worlds, PERSIS shows the different sides to its character: subtle and harmonious or distinctive and elegant. The carcass perfectly uses different material thicknesses – it is tapered towards the front, thus providing a fine frame. Its edges are of exceptional quality: the transitions are meticulously crafted, ensuring a beautiful overall look.


Contents

	Page
Range introduction, lists of versions	2-3
Suggested combinations	4-6
Lowboards, sideboards	8-9
Highboards, cabinets	10
Wall units, cabinet rear wall	11
Intermediate bookshelves, top bookshelves, wall shelves	12
Media accessories for lowboards, cable apertures, column system, flat screen supports	14-15
Accessories for units	16
Lamps, remote control	17
Dining rooms, coffee tables	18
General information:	
Special-sized products, special articles	19
Switch options for lamps	20-21
Important notes: quality of walls / assembly instruction	22

Lists of versions

Model no.	Carcass and front	Price group	Model no.	Accent versions: Carcass / Front	Price group
806 807	Solid oak natura Solid oak anthracite	I I	806 807 731 732	Solid oak natura / solid oak natura Solid oak anthracite / solid oak anthracite Solid oak natura / rear-printed glass relief pearlescent grey Solid oak anthracite / rear-printed glass relief anthracite	I I II II

Explanation of versions



Important notes

Accent versions:
Carcase in solid oak natura, front of rear-printed glass relief pearlescent grey or carcase in solid oak anthracite, front of rear-printed glass relief anthracite. Changing versions between carcase and front is not possible.

Glass versions:
Glass fronts, glass shelves behind fronts and glass shelves of bookshelves of clear glass

Metal substructures, frame profiles:
Metal substructures and frame profiles (always in the same version) in quartz structured lacquer for the solid oak natura version or in anthracite structured lacquer for the solid oak anthracite version. Please state the required version clearly in the order! Metal substructures incl. plinth adjusters.

Standard interior fittings:
Fitted wooden shelves are fitted behind doors at 2 Raster intervals and fitted glass shelves are fitted behind glass doors.

Drawer frames in carcase version

Wall units:
Wall units always incl. wall bracket


Combinations of floor and wall units:
If floor and wall units are combined within an arrangement, there must not be any skirting boards in the room near the floor units, otherwise they must be removed.

Max. load:
Max. load of wooden and glass shelves (up to 70.4 cm width) as well as drawers: 25 kg
Max. load of wooden and glass shelves (between 70.4 and 105.6 cm width): 15 kg;
from 105.6 cm width: 10 kg
Max. load of cover shelves: 35 kg per metre length for floor units. Please also note any maximum loads which may be stated in the type list for the individual units!

hülsta-Push-to-open: Drawers, flaps and doors with hülsta-Push-to-open

Information on the sketches

Split drawer frames:
Split drawer frames are used for drawers in front widths of 140.4 cm, 175,6 cm and 210,8 cm (the partitions are shown by dotted lines in the sketches). The front widths of the drawers are illustrated at the sketches of the units so that you can order suitable accessories for the drawers.



Wall fitting

Important notes: Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units. That is why wall mounting should only be carried out by properly trained and qualified fitters. hülsta supplies materials for mounting units on walls for nearly all the units and which should be used for safety and for constructional reasons. The assembly materials supplied by hülsta (plugs, screws) are only suitable for fitting components on to concrete in firmness class C12/15. For other materials (please see separate materials table in the wall composition chapter) we provide you with an assembly mortar set as an extra order. Please note that this assembly mortar set is also only suitable for the materials listed in the materials table. If walls are made up of other materials (e.g. plastered or lighter wall materials), one should use another method of mounting better suited to the load on site. Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. For the reasons stated above it is absolutely essential to enquire about the composition of any walls before signing any contracts.

Wall units

If lowboards are included as wall units, a maximum load per unit of 15 kg per metre must not be exceeded for reasons of stability! Max. load 15 kg per metre:

- 181.8 cm width: 25 kg
- 217.0 cm width: 30 kg
- 252.2 cm width: 30 kg
- 287.4 cm width: 35 kg

The wall units can only be fitted on absolutely solid walls. Light masonry is not suitable for this purpose.

For each project please remember to leave a 2.0 cm gap at the top to be able to mount units.

Labelling in type list drawings / assembly notes for wall units

Labelling in type list drawings / assembly notes for wall units
The majority of units have two wall mounting points (= number of base plates), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= base plates) is required, this is marked in the drawings in the type list with numbers in black boxes. Please be sure to note here the information and notes in the "Wall composition" chapter!

3
4

Notes on delivery

Notes on delivery:
The majority of the units are delivered standard as **fully connected units (glued)** so that the carcase **cannot be disassembled**. There are however some **exceptions** to this rule:

Some carcasses are delivered as complete units but can be **disassembled into individual sections** in the final customer's home. These types are marked with a **1** in the type list.







Some carcasses are delivered **in individual sections** because of their size. These types are marked with a **2** in the type list.

The fronts with the number **2** are delivered separately and can therefore always be (dis-) assembled.

Suggested combinations

Dark grey shading
in the sketches
= Accent version







As an alternative to planning an individual unit from the complete range there is the possibility of choosing from specially suggested combinations. This eases planning. Incorporating accessories can enhance the suggested combinations. These are charged extra.

	
<p>as illustr. v. versa</p> <p>980001</p> <p>Price gr. I - II -</p>	<p>980002 981002</p> <p>-</p>
	
<p>as illustr. v. versa</p> <p>980003 981003</p> <p>Price gr. I - II -</p>	<p>980004 981004</p> <p>-</p>
	
<p>as illustr. v. versa</p> <p>980005 981005</p> <p>Price gr. I - II -</p>	<p>980006 981006</p> <p>-</p>

Suggested combinations

PERSIS


As an alternative to planning an individual unit from the complete range there is the possibility of choosing from specially suggested combinations. This eases planning. Incorporating accessories can enhance the suggested combinations. These are charged extra.

			
as illustr. v. versa	980007 981007	980008 981008	
Price gr. I II	- -	- -	
			
as illustr. v. versa	980009 981009	980010 981010	
Price gr. I II	- -	- -	
			
as illustr. v. versa	980011 981011	980012 981012	
Price gr. I II	- -	- -	

Suggested combinations

Dark grey shading
in the sketches
= Accent version

As an alternative to planning an individual unit from the complete range there is the possibility of choosing from specially suggested combinations. This eases planning. Incorporating accessories can enhance the suggested combinations. These are charged extra.











as illustr. v. versa	980013 981013	
Price gr. I II	- -	



Lowboards and sideboards

Dark grey shading
in the sketches
= Accent version



Lowboards 55.4 cm high (57.2 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep	 181.8 cm wide			 217.0 cm wide					
	Flap hinge at bottom		Left: 1 door Centre: 1 flap Right: 1 door	Left: 1 door Centre: 1 drawer Right: 1 door	Left: 1 door Centre: 2 flaps Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer Right: 1 door	Left: 1 door Centre: 2 drawers Right: 1 door	
	Centre below: Flap in accent version	Price gr. I II	31828 - -	31818 - -	32128 - -	32138 - -	32148 - -	32118 - -	
	Centre below: Drawer in accent version	Price gr. I II	31821 - -	31811 - -	32121 - -	32131 - -	32141 - -	32111 - -	
When used as wall units: Max. load: 40 kg									
Sideboards 73.0 cm high (74.8 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep	 181.8 cm wide			 217.0 cm wide					
	Flap hinge at bottom		Left: 1 door Centre: 1 flap; 1 drawer Right: 1 door	Left: 1 door Centre: 1 drawer; 1 drawer Right: 1 door	Left: 1 door Centre: 2 flaps; 2 drawers Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap; 2 drawers Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer; 2 dra- wers Right: 1 door	Left: 1 door Centre: 2 drawers; 2 drawers Right: 1 door	
	Centre: Flap in accent version	Price gr. I II	41828 - -	41818 - -	42128 - -	42138 - -	42148 - -	42118 - -	
	Centre: Drawer in accent version	Price gr. I II	41821 - -	41811 - -	42121 - -	42131 - -	42141 - -	42111 - -	
When used as wall units: Max. load: 40 kg									
Wooden plinth 8.8 cm high The units can be planned optionally on a wooden plinth. In this case the plinth adjusters are omitted.			 for 181.8 cm width			 for 217.0 cm width			
	Price gr. I		2182 -			2212 -			
Metal substructure incl. plinth adjusters; 19.4 cm high The units can be planned optionally on a metal substructure. In this case the plinth adjusters are omitted.			 for 181.8 cm width			 for 217.0 cm width			
	Price gr. I		2181 -			2211 -			
Wall bracket If units are to be included as wall units or stacked on top of one another, a wall bracket must be ordered.	Price gr. I		2183 -			2213 -			









Notes on delivery:
Please see here the information on range introduction pages.

1
2

Assembly notes for wall units:
Please be sure to note here the information and notes in the "Wall composition" chapter!










3
4

PERSIS







			 252.2 cm wide				 287.4 cm wide			
	Flap hinge at bottom		Left: 1 door Centre: 2 flaps Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer Right: 1 door	Left: 1 door Centre: 2 drawers Right: 1 door	Left: 1 door Centre: 2 flaps Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer Right: 1 door	Left: 1 door Centre: 2 drawers Right: 1 door
	Centre below: Flap in accent version	Price gr. I II	32528 - -	32538 - -	32548 - -	32518 - -	32828 - -	32838 - -	32848 - -	32818 - -
	Centre below: Drawer in accent version	Price gr. I II	32521 - -	32531 - -	32541 - -	32511 - -	32821 - -	32831 - -	32841 - -	32811 - -
			 252.2 cm wide				 287.4 cm wide			
	Flap hinge at bottom		Left: 1 door Centre: 2 flaps; 2 drawers Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap; 2 drawers Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer; 2 drawers Right: 1 door	Left: 1 door Centre: 2 drawers; 2 drawers Right: 1 door	Left: 1 door Centre: 2 flaps; 2 drawers Right: 1 door	Left: 1 door Centre: 1 drawer, 1 flap; 2 drawers Right: 1 door	Left: 1 door Centre: 1 flap, 1 drawer; 2 drawers Right: 1 door	Left: 1 door Centre: 2 drawers; 2 drawers Right: 1 door
	Centre: Flap in accent version	Price gr. I II	42528 - -	42538 - -	42548 - -	42518 - -	42828 - -	42838 - -	42848 - -	42818 - -
	Centre: Drawer in accent version	Price gr. I II	42521 - -	42531 - -	42541 - -	42511 - -	42821 - -	42831 - -	42841 - -	42811 - -
			 for 252.2 cm width				 for 287.4 cm width			
		Price gr. I	2252 -				2282 -			
			 for 252.2 cm width				 for 287.4 cm width			
		Price gr. I	2251 -				2281 -			
		Price gr. I	2253 -				2283 -			

Highboards








Dark grey shading
in the sketches
= Accent version

Highboards 143.4 cm high (145.2 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep Cannot be fitted as a wall unit!			 34,8 34,8 74.6 cm wide		 52,4 34,8 92.2 cm wide		 70,0 34,8 109.8 cm wide	
	Flap hinge at bottom		Left: 1 flap, 1 glass door, 1 drawer Right: 1 door		Left: 1 flap, 1 glass door, 1 drawer Right: 1 door		Left: 1 flap, 1 glass door, 1 drawer Right: 1 door	
		as illustr. v. versa	97511 97512 - -		99211 99212 - -		91111 91112 - -	
Wooden plinth 8.8 cm high The units can be planned optionally on a wooden plinth. In this case the plinth adjusters are omitted.			 for 74.6 cm width		 for 92.2 cm width		 for 109.8 cm width	
	Price gr.		272 -		292 -		2112 -	
Metal substructure incl. plinth adjusters; 19.4 cm high The units can be planned optionally on a metal substructure. In this case the plinth adjusters are omitted.			 for 74.6 cm width		 for 92.2 cm width		 for 109.8 cm width	
	Price gr.		271 -		291 -		2111 -	










Cabinets

Cabinets 178.6 resp. 213.8 cm high (180.4 resp. 215.6 cm high incl. 1.8 cm high plinth adjusters), 45.0 cm deep Cannot be fitted as a wall unit! Cannot be fitted on a wooden plinth or metal substructure in 213.8 cm height!	178.6 cm high				213.8 cm high			
			 34,8 34,8 74.6 cm wide				 52,4 34,8 92.2 cm wide	
			Left: 1 glass door, 2 drawers Right: 1 door				Left: 1 glass door, 2 drawers Right: 1 door	
Wooden plinth 8.8 cm high The units can be planned optionally on a wooden plinth. In this case the plinth adjusters are omitted.			 for 74.6 cm width				 for 92.2 cm width	
	Price gr.		272 -				292 -	
Metal substructure incl. plinth adjusters; 19.4 cm high The units can be planned optionally on a metal substructure. In this case the plinth adjusters are omitted.			 for 74.6 cm width				 for 92.2 cm width	
	Price gr.		271 -				291 -	

Wall units



Wall units 37.8 cm high; 45.0 cm deep	 181.8 cm wide								 217.0 cm wide		 252.2 cm wide		 287.4 cm wide	
	Flap hinge at bottom	1 door; 1 drawer; 1 door	1 door; 1 flap; 1 door	1 door; 1 drawer; 1 door	1 door; 1 flap; 1 door	1 door; 1 drawer; 1 door	1 door; 1 flap; 1 door	1 door; 1 drawer; 1 door	1 door; 1 flap; 1 door					
		21811	21818	22111	22118	22511	22518	22811	22818					
	Price gr. I	-	-	-	-	-	-	-	-					
	II	-	-	-	-	-	-	-						
Max. load: 40 kg														
Wall units or wall assembly: See here the information on page 3														
Wall units 73.0 resp. 178.6 cm high; 35.0 cm deep	73.0 cm high				178.6 cm high									
	 145.0 cm wide		 145.0 cm wide		 37.8 cm wide									
					L									
Max. load: 40 kg	Flap hinge at bottom	2 flaps; 1 glass door		2 flaps; 1 glass door		1 door								
	as illustr. v. versa	414181 414182		414281 414282		10311 L 10312 R								
	Price gr. I	-		-		-								
Wall units or wall assembly: See here the information on page 3														

Cabinet rear wall



Cabinet rear wall of rear-lacquered structured glass in wood look Please state the required version clearly in the order!	for highboards compartment height: 70.4 cm			for cabinets compartment height: 105.6 cm		for cabinets compartment height: 140.8 cm		
								
	Compartment width: 35 cm	Compartment width: 52 cm	Compartment width: 70 cm	Compartment width: 35 cm	Compartment width: 52 cm	Compartment width: 35 cm	Compartment width: 52 cm	
	Price gr. II	439 -	459 -	479 -	639 -	659 -	839 -	859 -
	for wall units compartment height: 70.4 cm							
								
	Compartment width: 32.9 cm		Compartment width: 86.1 cm					
	Price gr. II	429 -	449 -					

Intermediate bookshelves



Dark grey shading
in the sketches
= Accent version

Intermediate bookshelves 35.2 resp. 71.1 cm high 45.0 cm deep with frame profile and rear wall in accent version LED frame profile lamp see page 17	35.2 cm high		71.1 cm high; with 1 glass shelf	
				
	70.6 cm wide		70.6 cm wide	
Price gr. I II	2700		4700	
	-		-	
	-		-	

Top bookshelves

Top bookshelves 71.1 resp. 107.1 cm high 45.0 cm deep with frame profile and rear wall in accent version LED frame profile lamp see page 17	71.1 cm high; with 1 glass shelf		107.1 cm high; with 2 glass shelves	
				
	70.6 cm wide		70.6 cm wide	
Price gr. I II	4710		6710	
	-		-	
	-		-	

Wall shelves

Wall shelves 2.5 cm thick; 24.0 cm deep for fitting anywhere on walls					
		146.6 cm wide	181.8 cm wide	217.0 cm wide	252.2 cm wide
		Max. load: 10 kg	Max. load: 10 kg	Max. load: 15 kg	Max. load: 15 kg
		1424	1824	2124	2524
	Price gr. I	-	-	-	-
This luminaire contains built-in LED lamps of the energy classes A+++ to A. The lamps cannot be changed in the luminaire. 12 V			LED lamps incl. footswitch. A remote control unit is possible for operation (against a surcharge).		
LED lamps for wall shelves					
		for 146.6 cm width	for 181.8 cm width	for 217.0 cm width	for 252.2 cm width
		9.6 W	13.0 W	16.4 W	20.2 W
		145	175	215	245
	Price gr. I	-	-	-	-

Possible arrangements

Notes on delivery:
Please see here the information on range introduction pages.

1
2

Assembly notes for wall units:
Please be sure to note here the information and notes in the "Wall composition" chapter!

3
4

PERSIS









Media accessories for lowboards







IR repeater set

<p>IR repeater set Infrared signal transmission set for operating media units behind wooden/lacquered fronts. You can operate all the units in one compartment with one set. The following applies:</p> <ul style="list-style-type: none">• One set must be used in each compartment. 2 transmitters can also be installed in large compartments in order to increase performance. In this case only one additional transmitter needs to be ordered.• The transmitter must be placed in the direct vicinity of the receiver eye.• Transmittable IR frequency band 20 – 60 kHz• Up to 3 transmitters can be combined with one receiver. <p>It is possible to use 3 transmitters via 1 receiver including Master box. This enables simultaneous operation of 3 different furniture compartments or in critical situations it allows fitting out one furniture compartment with several transmitters in order to increase the performance in this compartment or to operate 2 end units placed next to one another.</p> <p>The IR repeater set consists of:</p> <ul style="list-style-type: none">• 1 receiver eye (Ø 3.0 cm) incl. standing bracket• 1 electrical transmitter• 1 plug EVG 12 V• Cable clips <p>Please note the details stated in the operating instructions!</p>	
<p>IR repeater set 1 receiver eye and 1 transmitter incl. standing bracket</p>	
<p>2001 -</p>	
<p>Extra transmitter</p>	
<p>2003 -</p>	

Cable apertures






	<p>Cable aperture K1 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear of the top shelf. The position is in the centre of the compartment, distance from centre of aperture to rear edge of unit: 10.0 cm.</p>	<p>K1 -</p>
	<p>Cable aperture K2 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the rear wall of the lowboard. Positioned at centre of compartment.</p>	<p>K2 -</p>
	<p>Cable aperture K7 silver-coloured; 7.0 x 12.0 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The position is in the centre of the compartment, flush with the rear edge of the unit.</p>	<p>K7 -</p>
	<p>Cable aperture K8 silver-coloured; 12.8 x 3.2 cm It is possible to fit a cable aperture in the top shelf of the lowboard. The cable aperture can be made at the rear rim of the top shelf. Positioned in centre of compartment.</p>	<p>K8 -</p>
	<p>Cable aperture K9 13.0 x 1.6 cm It is possible to fit a cable aperture in a fitted shelf. The cable aperture can be made at the rear rim of the fitted shelf. Positioned in centre of compartment.</p>	<p>K9 -</p>
	<p>Cable aperture K20 silver-coloured; Ø 8.0 cm It is possible to fit a cable aperture in the partitions of the lowboard.</p>	<p>K20 -</p>

Column system, flat screen supports


<p>Column system consisting of a metal column (for fitting anywhere on wall) and of audio/DVD support(s), for fitting anywhere on column.</p> <p>Example of use:</p> 	<p>Columns of metal; for fitting anywhere on walls above top rim of plinth slot; cables can be laid and hidden at any height; audio/DVD supports can be fitted anywhere on the column.</p> 	<p>Audio/DVD support of metal; can be positioned at any height on the column and be adjusted to suit audio/DVD players of any size; with rubber padding at front to prevent units from slipping; max. load: 10 kg</p> 						
	<table><tr><td>36.8 cm high</td><td>64.1 cm high</td></tr><tr><td>9201</td><td>9202</td></tr><tr><td>-</td><td>-</td></tr></table>	36.8 cm high	64.1 cm high	9201	9202	-	-	<p>9203</p> <p>-</p>
36.8 cm high	64.1 cm high							
9201	9202							
-	-							
<p>Flat screen support WTL6 The flat screen support can be adjusted 3-dimensionally. It is suitable for flat screens with a screen diagonal of 102-216 cm (40“-85“); max. load: 45 kg. Suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 200 x 200 mm max.: 600 x 400 mm</p> 	<p>Flat screen support THIN 345, ideally adaptable The flat screen support can be adjusted 3-dimensionally. It is suitable for flat screens with a screen diagonal of 81-140 cm (32“-55“) and a maximum depth of 4.5 cm; max. load: 25 kg. Go to www.vogels.com to check if your flat screen can be fitted on this flat screen support. Enter the name THIN 345. After a few steps you can see if your flat screen TV is compatible with the flat screen support. Not suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 100 x 100 mm max.: 600 x 400 mm</p> 	<p>Flat screen support THIN 315 The flat screen support can be angled up to a max. 15°. It is suitable for flat screens with a screen diagonal of 102-165 cm (40“-65“) and a maximum depth of 5.0 cm; max. load: 25 kg. Go to www.vogels.com to check if your flat screen can be fitted on this flat screen support. Enter the name THIN 315. After a few steps you can see if your flat screen TV is compatible with the flat screen support. Not suitable for Curved TV's. Flat screen support compatible with VESA Norm standard: min.: 100 x 100 mm max.: 600 x 400 mm</p> 						
for fitting anywhere on walls	for fitting anywhere on walls	for fitting anywhere on walls						
9704	9304	9504						
-	-	-						

Accessories for units







Accessories for drawers

 Tableau lined with grey fabric	for 34.8 cm front width	for 52.4 cm front width	for 70.0 cm front width	for 105.2 cm front width	for ½ drawer, 140.4 cm wide, and 70.0 cm front width	for ½ drawer, 175.6 cm wide, and 87.6 cm front width	for ½ drawer, 210.8 cm wide
	8620 -	8621 -	8622 -	8623 -	8624 -	8625 -	8626 -
 CD holder for drawers Please state exactly in your order and drawing in which 2 Raster drawer the CD holder is to be fitted.	for 36 CD's	for 54 CD's	for 64 CD's	for 112 CD's	for 64 CD's	for 96 CD's	for 112 CD's
	8420 -	8421 -	8422 -	8423 -	8424 -	8425 -	8426 -
 DVD/Blu-Ray holder for drawers Please state exactly in your order and drawing in which 2 Raster drawer the DVD/Blu-Ray holder is to be fitted.	for 12 DVD's	for 24 DVD's	for 33 DVD's	for 44 DVD's	for 33 DVD's	for 44 DVD's	for 44 DVD's
	8320 -	8321 -	8322 -	8323 -	8324 -	8325 -	8326 -
 Cutlery box of metal, lined with grey fabric inside; incl. compartments	17.6 cm wide			35.2 cm wide			
	855 -			856 -			
 Cutlery holder lined with grey fabric, for fitting in drawers Set 1: for 60 pieces of cutlery Set 2: for 17 serving utensils	Set 1: for standard cutlery like spoons, forks, knives, etc.			Set 2: for sauce ladles, cake forks, cake servers, etc.			
	116 -			117 -			

Fitted shelves

 Fitted shelf 1.9 cm thick	for 34.8 cm front width	for wall units type 10311, 10312
	134 -	144 -

Lamps

This luminaire contains built-in LED lamps of the energy classes A++ to A. The lamps cannot be changed in the luminaire. 12 V		LED lamps incl. footswitch. A remote control unit is possible for operation (against a surcharge).		
 <p>Integrated LED spotlight Ø 7.1 cm; for fitting in units Later fitting is not possible.</p>	2.9 W			
	7941 -			
 <p>LED light panel 1.9 cm thick, 3.0 cm deep; for fitting under glass shelves Later fitting is not possible.</p> <p>under glass shelves</p>	for 35.2 cm width	for 52.8 cm width	for 70.4 cm width	
	2.4 W 325 -	3.5 W 525 -	5.1 W 825 -	
 <p>LED frame profile lamp LED lamp fitted in the frame profile of intermediate and top bookshelves Later fitting is not possible.</p>	for intermediate bookshelf type 2700	for intermediate bookshelf type 4700 and top bookshelf type 4710	for top bookshelf type 6710	
	6.8 W  725 -	13.5 W  745 -	20.2 W  765 -	

Radio remote control with change of colour temperature

The lamps are normally operated by an external foot switch. The colour temperature of the LED lamps is cold white if a foot switch is used. A 4-channel radio remote control is also available as an alternative, which is charged extra. Several lamps can be operated with each of the 4 channels. All 4 channels can be dimmed separately at the push of a button. The colour temperature of all 4 channels can be set to any level from cold white (approx. 6500 kelvin = the basic setting of the LED lamps) to warm white (approx. 2700 kelvin). If warm white is required, a radio remote control must be ordered. It is also possible to switch all channels on and off simultaneously with the "all on" or "all off" buttons. The radio remote control consists of one transmitter and one receiver. If several receivers are required because of the arrangement of the units, these and the corresponding cables are provided ex-works (no surcharge). The foot switch is omitted when the radio remote control is used.

2119
-

DINING Dining tables and chairs

DINING

hülsta offers a room concept to meet all requirements in comfort, beauty of form and attractiveness with a comprehensive collection of dining room tables and chairs.

The **dining tables** in a wide variety of sizes (with and without pullout function) in all wood surface versions and in contemporary designs, as well as the **dining chairs** that can be combined individually using different armrests, comfort features, high-grade cover fabrics (leather, textiles) and metal surfaces can all be found in the “**DINING**” type list.



Coffee tables CT 210

Coffee tables CT 210

Soft curves characterise the classic yet extravagant design of the CT 210 coffee table: The solid table top is tapered towards the edge, instead of hard angles you will find soft transitions, providing a beautiful look and feel. With its solid quality, elegant materials, timeless design and convincing functionality, the CT 210 perfectly fits into any home.

You will find the CT 210 coffee table as well as other coffee tables in the “**Coffee tables**” type list.



Coffee tables

Coffee tables

hülsta offers a comprehensive **collection of coffee tables**, which not only match the hülsta furniture ranges perfectly but can also be combined with other products that are available on the market. You will find these coffee tables in a number of designs, sizes and versions in the “**Coffee tables**” type list.



PERSIS

Special-sized products are possible on request.
Please get in touch with your customer advisor.

Special articles

Cover panels for side and top panelling of fitted wardrobes (support construction and fitting materials must be acquired on site).		
Basic price per order	9901	-
+ price per m ² lacquer or veneer	990	-
Veneer match with fronts can not be guaranteed.		
 Individual special-sized products If the special-sized product that you require is so unusual that it cannot be illustrated with the many special sized products that we already provide and charge for, then we will quote you the price using a 33 unit type factor. In your order please state for us the relevant enquiry number and the 33 unit type factor stated.		
	33	-

Special colours; Note on „Blue Angel“ / Emissions label of DGM

Special colours
All the hülsta lacquer colours are possible for nearly all the hülsta ranges.
Availability and prices on request.

Note on „Blue Angel“ (RAL-UZ 38) and Emissions label of DGM (Class A)
It is possible that the requirements of the „Blue Angel“ and the DGM Emissions Label cannot be met by some of the lacquer colours in price groups III and IV (see here the different lacquer versions in the NEO range), depending on the colour mix (surface ratio of these colours in the corresponding order). However, the legal requirements are definitely met in all cases!

Switch options for lamps:
Radio remote control with change of colour temperature

Radio remote control with change of colour temperature

The lamps are normally operated by an external foot switch. The colour temperature of the LED lamps is cold white if a foot switch is used. A 4-channel radio remote control is also available as an alternative, which is charged extra. Several lamps can be operated with each of the 4 channels. All 4 channels can be dimmed separately at the push of a button. The colour temperature of all 4 channels can be set to any level from cold white (approx. 6500 kelvin = the basic setting of the LED lamps) to warm white (approx. 2700 kelvin). If warm white is required, a radio remote control must be ordered. It is also possible to switch all channels on and off simultaneously with the “all on” or “all off” buttons. The radio remote control consists of one transmitter and one receiver. If several receivers are required because of the arrangement of the units, these and the corresponding cables are provided ex-works (no surcharge). The foot switch is omitted when the radio remote control is used.

The following points must be noted with the radio remote control:

- The receiver must be positioned behind a rear wall or under plinth shelves (at least 20 mm space required under plinth shelves).
- The total wattage power of all lamps included per receiver must not exceed 30 W.
- 4 channels = 4 light groups
- 1 light group = x lights
- All lamps within a light group can be dimmed to the same brightness.
- The change of the colour temperature takes place for all lamps in all light groups.
- The radio remote control is not suitable for equipment operating on 110 V.

Please be sure to note the operating and programming instructions!

4-channel radio remote control with change of color temperature



4-channel radio remote control
with change of color temperature

Type	2119	-
------	------	---

Examples of use (schematic diagrams)

Example 1

Lights inside a unit


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlight in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps in the open compartment

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlight in the right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Example 2

Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlight and the LED light panels in the left cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the LED spotlamps and the LED light panels in the centre cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the LED spotlight and the LED light panels in the right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Example 3

Lights in units set apart


Channel 1 operates (and dims) all the lights in light group 1, i.e. the LED spotlamps in the left, centre and right cabinet

Channel 2 operates (and dims) all the lights in light group 2, i.e. the top LED light panels in the left, centre and right cabinet

Channel 3 operates (and dims) all the lights in light group 3, i.e. the bottom LED light panels in the left, centre and right cabinet

Notes:

The total wattage power of all lamps included per receiver must not exceed 30 W. The change of the colour temperature takes place for all lamps in all light groups.



Important notes

Wall composition / assembly instruction









Important notes:
The composition of walls must be ascertained before concluding a contract and be checked by a qualified fitter before assembly takes place.

Assembly may only be carried out by a qualified fitter under careful observation of the assembly instructions.

The plastic Rawl plugs supplied by hülsta as a standard set are only suitable for concrete \geq C12/15, if the wall composition and compression strength corresponds to the table below. Under no circumstances must a unit be assembled on light masonry.

Furthermore, we provide a mounting set with assembly mortar for the types of walls listed below (see assembly mortar set below). Again, assembly must be carried out by a qualified fitter under careful observation of the wall composition and assembly instruction. The compression strength levels stated below must be met under all circumstances.

Materials table
with a description of which sets are to be used with the following types of walls:

Standard set	Assembly mortar set only suitable for the materials stated below!			
Concrete C12/15 Compression strength \geq 15 N/mm ² 		Building bricks Mz 12 Compression strength \geq 12 N/mm ²		Solid blocks of light concrete V2 Compression strength \geq 2 N/mm ²
		Limestone blocks KS 12 Compression strength \geq 12 N/mm ²		Perforated blocks of light concrete Hbl 2 Compression strength \geq 2 N/mm ²
		Perforated sand lime bricks KSL12 Compression strength \geq 12 N/mm ²		Aerated concrete PP2 Compression strength \geq 2 N/mm ²
		Vertically perforated bricks HLz 12 Compression strength \geq 12 N/mm ² Bulk density \geq 1.0 kg/dm ³		

A different and more suitable type of mounting must be chosen by a qualified fitter in all other cases. hülsta cannot accept any responsibility for the choice of any other types of mounting! Please note that if the units are not mounted properly on the wall, there is a risk of the units falling down or tipping over – especially when alternative mounting materials acquired on site have been used. Generally speaking, you as a dealer/qualified fitter are responsible for the correct wall mounting of the units.



Mounting sets

Labelling in type list drawings / assembly notes for wall units
The majority of units have two wall mounting points (= number of support boards), if these are to be fitted as wall units. This is not explicitly mentioned in the type list. If a different number of wall mounting points (= support boards) is required, this is marked in the drawings in the type list with numbers in black boxes. Every support board requires four mounting screws.

3 = 3 support boards
4 = 4 support boards, etc.

One **assembly mortar set** is sufficient for up to a maximum of 3 support boards or 4 wall side-panels.

Important note: Depending on the composition of the wall (see wall types illustrated above), assembly must be carried out using the special assembly mortar set and a standard trade mastic tool which are the basic essentials for safe and clean workmanship.

Standard set
The standard set consists of 4 plastic Rawl plugs and 4 mounting screws and is sufficient for 1 support board. The standard sets are included in the packet of fittings to match the number of support boards.

<p>Assembly mortar set for up to a maximum of 3 support boards consisting of:</p> <p>9x injection retaining sleeve 9x screw-in sleeve 1x injection cartridge 2x static mixer 1x assembly instructions</p> <p>Please use the mounting screws from the standard set (supplied free of charge).</p>	<p>Example of order:</p> <ul style="list-style-type: none">• Add up number of support boards for all existing unit types• Divide the sum by “3”• Round up the result to a full number <p>= Number of assembly mortar sets required</p>	<p>M2</p> <p>-</p>
---	---	---------------------------

Your Hotline to hülsta

Do you have any questions or require any alterations to your order confirmation?
Do you have any questions on our products or your current order?
Do you have any complaints about supplied goods or required replacement parts?
Contact Telephone: +49 (0) 2563 / 86-1627 • email: orders@huelsta.com

Do you have any questions, suggestions or wishes for the **hülsta product seminars**?
Contact Telephone: +49 (0) 2563 / 86-1493 • email: seminare@huelsta.com

hülsta Planning Service

Your furn plan planning is so complex that you need our support? We have created the hülsta Planning Service for this kind of situation. hülsta employees will check your planning as quickly as possible. The customer gets a planning that will inspire him!

hülsta Planning Service

Tel.: +49 (0) 2563 / 86-1060

Fax: +49 (0) 2563 / 86-1000

Mail: Planungsservice-Handel@huelsta.com

Mondays to Fridays from 9.00 a.m. until 5.00 p.m.

Special wishes? Come to us!

Maximum individuality! – Maximal flexibility! – hülsta makes most of your special wishes possible.

And if you do have a wish which is not quite so easy to implement, just give us a call or send us a mail or a fax. We have our own hülsta "Special Wishes Team" who are there to help you realise just these customer requests. These colleagues are professionals when it comes to special products. They plan and calculate the products possible for you and even develop an alternative suggestion if the idea should turn out to be technically impossible.

Here is an overview of the hülsta range of special wishes:

- A lot of special products can be ordered simply via the type list
- Special-sized products are planned simply and professionally
- Competent colleagues advise you by phone, by fax and by mail
- You will be sent alternative suggestions if the idea is technically impossible
- Many special-sized products are available without a surcharge
- Specially qualified carpenters and technicians implement your plans perfectly

hülsta Special Wishes Team

Tel.: +49 (0) 2563 / 86-1060

Fax: +49 (0) 2563 / 86-1000

Mail: Sonderwunsch@huelsta.com

We are open Saturdays for you, too!

Our **Saturday hotline** is available from **10.00 a.m. until 5.00 p.m.**

Telephone: +49 (0) 2563 / 86-1800

The hülsta Sales Department is available
mondays to Fridays from 9.00 a.m. until 5.00 p.m.

hülsta PERSIS

Stand: E 1. 2021

Design and concept legally protected, subject to error and alterations to construction, colour and materials by way of technological progress.

hülsta-werke · Karl-Hüls-Straße 1 · D-48703 Stadthoehn
Tel. +49 (0) 2563 / 86-0 · Fax +49 (0) 2563 / 86-1000
www.huelsta.com

